


## LAMINATED LOG PLANKS



### Planks made of 2 pcs Sawn timber used

dimensions	product	pcs	dimensions
94 x 175	LHA LHA/J	2	50 x 175
100 x 175	LHA LHA/J	2	54 x 175
120 x 175	LHA LHA/J	2	63 x 175
142 x 175	LHA LHA/J	2	75 x 175
94 x 200	LHA LHA/J	2	50 x 200
120 x 200	LHA LHA/J	2	63 x 200
142 x 200	LHA LHA/J	2	75 x 200
92 x 225	LHA LHA/J	2	50 x 225
118 x 225	LHA LHA/J	2	63 x 225
142 x 225	LHA LHA/J	2	75 x 225



### Planks made of 3 pcs Sawn timber used

dimensions	product	pcs	dimensions
186 x 225	LHA LHA/J	3	67 x 225
210 x 225	LHA LHA/J	3	75 x 225



### Planks made of 4 pcs Sawn timber used

dimensions	product	pcs	dimensions
236 x 225	LHA LHA/J	4	63 x 225
248 x 225	LHA LHA/J	4	67 x 225
280 x 225	LHA LHA/J	4	75 x 225



### Double layer planks Sawn timber used

dimensions	product	pcs	dimensions
186 x 284	LHA LHA/J	6	67 x 150
210 x 284	LHA LHA/J	6	75 x 150
248 x 284	LHA LHA/J	8	67 x 150
280 x 284	LHA LHA/J	8	75 x 150

Wood used:	Pine and spruce
Timber quality:	Combination of V- and VI-grades, "log graded timber"
Moisture:	16 % ± 2 %.
Finger jointing:	The joints are done to layers and will occur in different positions throughout the final product. The finger jointing has been certified and is continuously audited by an independent auditor according to product certification TR 20:2010. From the finger jointed layers, blue, rot, excess black knots, cracks and other similar defects will be removed.
Gluing:	Polyurethane, heart side of wood outwards. The quality of the gluing process has been certified and is continuously audited by an independent auditor according to product certification TR 21:2010.
Packing:	In bundles, plastic wrapped, plastic bands.

LHA	standard sawn lengths
LHA/J	finger jointed to the length specified by customer, max. length 12,2 m